RED

RT-SP 260 D

Stationary Planer

The RT-SP 260 D stationary planer is designed for high standards of accuracy and precision within its working range. Universal machining options include the squaring and truing up of rough timber or planing to exact thickness on the thicknessing table. The joint stop is horizontally adjustable and can be tilted through 45° for chamfering.
The knife shaft is equipped with two reversible planing knives for high performance – maximum chip depth 3 mm – and optimum, fine surfaces.
The sturdy base frame gives an excellent stability and offers a practical reservoir at the same time.

Features

- Powerful 400 V motor
- Selector switch for two operating modes (surfacing mode, thicknessing mode)
- Large aluminum feed table
- Infinitely adjustable aluminium parallel stop for exact results
- Connection for dust and chip extractor Ø 100 mm
- Complete with wheels and comfortable handles for easy transport
- Sturdy base frame including storage space

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved.
File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\4419921_01017.doc
Erstelldatum/create date: 29.01.2008 15:43:00Aktualisiert/up dated: 08.02.2008

RT-SP 260 D

Stationary Planer

Connection for dust and chip extractor Ø 100 mm

Combined switch and plug

Complete with wheels and comfortable handles for easy transport

Infinitely adjustable parallel stop for exact results, for chamfer tiltable up to 45°

Large massive aluminum feed table

Sturdy base frame
Incl. storage space

Logistic Information

Type:	**RT-SP 260 D**
Art.-No.:	44.199.21
Ident-No.:	01017
Bar code:	4006825 541076
Packing:	810 x 570 x 590 mm
Sales unit:	1 pc
20'':	112 pcs
40'':	224 pcs
40'' HC:	--- pcs
Weight:	90.0 kgs (gross)

Technical Data

Voltage:	400 V 3 ~ 50 Hz
Power:	2,800 W S6 40%
Idle speed (planing knives):	6,500 min^{-1}
Max. working width:	260 mm
Max. planing depth:	3 mm
Max. thicknessing depth:	3 mm
Max. thickness opening:	160 mm
Feeding speed:	5 m/min
Max. parallel guide tilt:	45°

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved.
File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\4419921_01017.doc
Erstelldatum/create date: 29.01.2008 15:43:00Aktualisiert/up dated: 08.02.2008